

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**LISTING OF CLAIMS:**

<sup>11</sup> / (Withdrawn) A process for forming the strippable glass fiber wall covering according to Claim ~~16~~<sup>1</sup>, said process comprising:

- (a) providing a glass fiber fabric,
- (b) forming a first dried coating on both sides of said glass fiber fabric that is applied from an aqueous dispersion comprising a starch and a polymeric latex binder, and
- (c) subsequently forming a second dried coating on said first dried coating on one side only of said glass fiber fabric that is applied from an aqueous dispersion consisting essentially of a paraffin wax and a rheology modifier with said second dried coating being capable of aiding in the removal of the wall covering from the wall.

<sup>3</sup> / (Previously Presented) A wall covering according to Claim ~~17~~<sup>1</sup>, wherein said glass fiber fabric is a woven fabric.

<sup>4</sup> / (Previously Presented) A wall covering according to Claim ~~17~~<sup>1</sup>, wherein said glass fiber fabric is a nonwoven.

11

12 ~~4~~. (Withdrawn) A process according to Claim ~~1~~, wherein the glass fiber fabric is supplied in roll form.

1

5 ~~5~~. (Previously Presented) A wall covering according to Claim ~~1~~, wherein said starch component of the first dried coating is potato starch.

1

6 ~~6~~. (Previously Presented) A wall covering according to Claim ~~1~~, wherein said polymeric latex binder component of the first dried coating is an acrylic latex binder.

1

7 ~~7~~. (Previously Presented) A wall covering according to Claim ~~1~~, wherein said first dried coating includes a cross-linking agent.

1

8 ~~8~~. (Previously Presented) A wall covering according to Claim ~~1~~, wherein said cross-linking agent of the first dried coating is a zirconium cross-linker.

1

9 ~~9~~. (Previously Presented) A wall covering according to Claim ~~1~~, wherein said first dried coating additionally includes pigment.

1

10 ~~10~~. (Previously Presented) A wall covering according to Claim ~~9~~, wherein said pigment of the first dried coating is titanium dioxide.

11

13 ~~11~~. (Withdrawn) A process according to Claim ~~1~~ wherein the aqueous dispersions of said first and second dried coatings are applied on a continuous process.

<sup>14</sup> ~~12~~. (Withdrawn) The process of Claim ~~1~~<sup>11</sup> wherein the drying of the glass fiber fabric in steps (b) and (c) is accomplished through the use of drying cylinders.

<sup>15</sup> ~~13~~. (Withdrawn) The process of Claim ~~1~~<sup>11</sup> wherein the drying of the glass fiber fabric in steps (b) and (c) is accomplished in air driers.

<sup>16</sup> ~~14~~. (Withdrawn) The process of Claim ~~1~~<sup>11</sup> wherein the application of said aqueous dispersions in steps (b) and (c) is accomplished through the use of a rotating screen applicator.

<sup>17</sup> ~~15~~. (Withdrawn) The process of Claim ~~1~~<sup>11</sup> wherein the applying of said aqueous dispersions in steps (b) and (c) is accomplished through the use of transfer rollers.

16. (Canceled)

<sup>1</sup> ~~17~~. (Currently Amended) A strippable glass fiber wall covering comprising a glass fiber fabric impregnated and coated on both sides with a first dried coating comprising a starch and a polymeric latex binder and having applied thereon a second dried coating to only one of the coated sides, whereby the second dried coating consists essentially of a paraffin wax and a rheology modifier and serves as a separation layer that facilitates the removal of said wall covering from a substrate, wherein the starch is present in an amount ranging from about 10 to 70% by wt. and the polymeric latex binder is present in an amount ranging from about 20 to 80% by

wt., based on the dried weight of the first coating, and wherein the paraffin wax is present in an amount ranging from about 80 to 99% by wt. and the rheology modifier is present in an amount ranging from about 1 to 20% by wt., based on the dried weight of the second coating.

18. (Canceled)

19. (Canceled)

~~2~~ <sup>1</sup> 20. (Previously Presented) The wall covering according to Claim ~~17~~, wherein the rheology modifier is an acrylic thickener, a polyurethane thickener or a cellulose thickener.